



QUALITY MEANS SUCCESS
LA QUALITE SIGNIFIE LE SUCCES
ISO 9001 / 2000



SBM 125



SBM 150



This new generation of SICAM Wheel Balancers have many features to ensure rapid and accurate wheel balancing of all passenger and light truck wheels, including alloy rims. Seven different balancing programs are provided, including split weight program, as well as an internal weight positioning gauge. The dual operator program allows the machine to be used by two different operators at the same time. The SBM 150 has the added feature of automatic data entry.




Cette nouvelle version d'équilibreur de roué SICAM. Elle contient sept différents programmes de balancement, incluant, le programme masse invisible, la règle de positionnement des autocollants. Le programme multi-opérateur permet l'utilisation de la machine par deux opérateurs simultanément. Le SBM 150 à l'avantage d'un système de mesure automatique effectuée avec les règles.



OPTIONAL



606300



606200



635800



627600

SPECIFICATIONS – DONNEES TECHNIQUES

Weight with casing Poids avec carter	single phase Moteur monophasé	Balancing speed (r.p.m.) Vitesse d'équilibrage	Wheel max weight Poids maxi de la roue	Wheel max diameter Diamètre maxi de la roue	Rim width Largeur de la jante	Rim Diameter Diamètre de la jante
285 lbs 129 kg	110V - 60 Hz	190 giri / min.	150 lbs	36"	1" to 20"	10" to 24"